

Safety Data Sheet



According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

Revision Date : 20.05.2015

1.1. Product identifier Product Name			
Product Name			
	: Artline Permanent Marker Color : (Black)		
	EK-250 Artline250 "0000	N	
1.2. Recommended use	of the chemical and restrictions on use		
Recommended use	: Permanent marker ink		
1.3. Details of the supplie	er of the safety data sheet		
Company Name Address Telephone Fax Contact (e-mail)	 Shachihata Inc. (U.S.A.) 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A. 1-800-541-9719 1-800-541-7166 <u>customerservice@xstamper.com</u> 		
1.4. Emergency telephor	ne number		
CHEMTREC 1-80			
	naterials or dangerous goods incident, Spill, leak, fire, exposure or accident)		
ECTION 2: Hazard(s) identification		
•	·		
2.1.1 Classification of the	According to OSHA 29 CFR 1910.1200 HCS 2012		
Specific target organ	/eye irritation, Category 1 H318 : Causes serious eye damage toxicity ; single exposure, Category 3 H335 : May cause respiratory irritation ract irritation, narcotic effects) H336 : May cause drowsiness or dizz :		
Signal word	: Danger		
Hazard statement	: Highly flammable liquid and vapour	(H225)	
	Causes serious eye damage	(H318)	
	May cause respiratory irritation	(H335)	
	May cause drowsiness or dizziness	(H336)	
Precautionary statemer	nt		
[Prevention]			
	t/sparks/open flames/hot surfaces No smoking.	(P210)	
Keep away from heat	Take precautionary measures against static discharge.		
Take precautionary n	es/protective clothing/eye protection/face protection.	(P280)	
Take precautionary n Wear protective glove Avoid breathing dust	es/protective clothing/eye protection/face protection. /fume/gas/mist/vapours/spray.	(P280) (P261)	
Take precautionary n Wear protective glove Avoid breathing dust Use only outdoors or	es/protective clothing/eye protection/face protection. /fume/gas/mist/vapours/spray. in a well-ventilated area.		
Take precautionary n Wear protective glove Avoid breathing dust/ Use only outdoors or Wash hands thoroug	es/protective clothing/eye protection/face protection. /fume/gas/mist/vapours/spray. in a well-ventilated area.	(P261)	
Take precautionary n Wear protective glove Avoid breathing dust/ Use only outdoors or Wash hands thoroug [Response]	es/protective clothing/eye protection/face protection. /fume/gas/mist/vapours/spray. in a well-ventilated area. hly after handling.	(P261) (P271)	
Take precautionary n Wear protective glove Avoid breathing duste Use only outdoors or Wash hands thoroug [Response] In case of fire	es/protective clothing/eye protection/face protection. /fume/gas/mist/vapours/spray. in a well-ventilated area. hly after handling. Use dry chemical powder,form or carbon dioxide for extinction.	(P261) (P271) (P264) (P370+P378)	
Take precautionary n Wear protective glove Avoid breathing dust/ Use only outdoors or Wash hands thoroug [Response] In case of fire : IF INHALED :	es/protective clothing/eye protection/face protection. /fume/gas/mist/vapours/spray. in a well-ventilated area. hly after handling.	(P261) (P271) (P264)	

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-250_black_b] 2/6

If eye irritation persists	: Get medical advice/attention.	(P337+P313)
IF ON SKIN (or hair)	: Remove/Take off immediately all contaminated clothing.	(P303+P361+P353)
	Rinse skin with water/shower.	
If skin irritation occurs	: Get medical advice/attention.	(P332+P313)
IF SWALLOWED	: Get medical advice/attention if you feel unwell.Rinse mouth.	(P301+P314+P330)
[Storage]		
Store in a well-ventilated	place. Keep container tightly closed.	(P403+P233)
[Disposal]		
Dispose of contents/container to waste in accordance with		
local/regional/ nationa	I/international regulation (to be specified).	
-		

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada : According to WHMIS


- 2.2.1 Classification of the substance or mixture
 - Class B2 : Flammable Liquids
 - Class D2B : Eye irritation
- 2.2.2 Label elements



2.2.3 Other hazards

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS)

2.3 Other information



SECTION 3: Composition/information on ingredients

Substance/Mixture : M Ingredients :	ixture			
Chemical Name / Composition CAS Classification (OSHA HCS 2012				
Generic name	weight %	Registry No.	Hazard Class	Hazard statement
Ethanol	25 ~ 35	64-17-5	Flam.Liq. 2	H225
1-methoxypropan-2-ol	20 ~ 30	107-98-2	Flam.Liq. 3 STOT.SE. 3	H226 H336
Ethyl lactate	20 ~ 30	97-64-3	Flam.Liq. 3 Eye Dam. 1 STOT.SE. 3	H226 H318 H335
Synthetic resin	1 ~ 10	Confidential	none	none
Dyestuff	10 ~ 20	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.

IF ON SKIN

: Remove/Take off immediately all contaminated clothing.Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice. [ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-250_black_b] 3/6

IF IN EYES	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
	easy to do.Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly.Moreover, do not give anything from the mouth to the patient when not conscious.Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Fire-fighting measures

- 5.1. Extinguishing mediaSuitable extinguishing mediaUnsuitable extinguishing mediaWater jet
- 5.2. Special hazards arising from the substance or mixtureFor initial stage extinction, carbon dioxide or dry chemical powder.When a fire extends, fire is extinguished by a large amount of water spray.Do not discharge extinguishing waters into the aquatic environment.
- 5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe area. Shut off all sources of ignition. No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.
 6.2. Environmental precautions Do not throw the leakage thing directly into environment
- 6.3. Methods and material for containment and cleaning up

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth,etc.), and then wipe off the waste well with waste cloth, and rag. In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

. .

Advice on safe handling	: Use with adequate ventilation.
	Avoid contact with skin, eyes and clothing.
	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Do not eat, drink or smoke when using this product.

Requirements for storage
areas and containers: Keep containers tightly closed and store in a cool and dry place.
Keep away from heat and flame,ignition source and sunlight.
Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

ACGIH (2013) Ethanol 1-methoxypropan-2-ol	STEL TWA	1000ppm 50ppm
OSHA PEL Ethanol	TWA	1000ppm
Canada Ontario Provincial Ethanol 1-methoxypropan-2-ol	STEL TWA	1000ppm 100ppm
Canada Quebec Provincial Ethanol	TWA	1000ppm

1-methoxypropan-	2-ol	TWA	100ppm	
8.2. Exposure controls Personal protective equipm	ent			
Respiratory Protection			ust ventilation, when in long use. ours. Wear mask to prevent organic gas, if necessary.	
Hand Protection	: Avoid c	ontact with har	ands. Wear safety gloves, if necessary.	
Eye Protection	: Avoid c	ontact with eye	yes. Wear safety glasses, if necessary.	
Skin Protection	: Avoid s	kin contact. W	Near personal protection apron,boots, if necessary.	
Environmental exposure co General advice	: Preven Preven	t further leakag	n entering drains. age or spillage if safe to do so. ninates rivers and lakes or drains inform respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties				
Appearance	: black liquid			
Odor	: minor solvent odor			
рН	: Not applicable			
Boiling point	: No data available			
Flash point	: 66.2 °F (19.0 °C) (closed cup)			
Relative Density (at 77 °F , 25 °C)	: 0.85 ~ 0.95 (g/cm ³)			
Solubility in Water	: Insoluble			

SECTION 10: Stability and reactivity

10.1. Reactivity

- No dangerous reaction known under conditions of normal use.
- 10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

- 10.3. Chemical stability
 - The product is stable.
- 10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

- 10.5. Incompatible Materials
 - No data available
- 10.6. Hazardous decomposition products
 - CO, CO_2

SECTION 11: Toxicological information

11.1. Information on toxicological et	ffects			
Acute toxicity	: LD/LC50 values that are relevant for classification			
	[Ethanol]			
	Oral-rat	LD50	7,060mg/kg	
	Inhalation-rat	LC50	20,000ppm/10h	
	[1-methoxypropa	n-2-ol]		
	Oral-rat	LD50	>5,000mg/kg	
	Dermal-rabbit		13,000mg/kg	
	Inhalation-rat	LC50	>7,559ppm/6h	
	[Ethyl lactate]			
	Oral-rat	LD50	2,500mg/kg	
	Inhalation-rat	LC50	>5,400mg/m ³ /8H	
Serious eye damage /eye irritation	: Category 1	Causes serious	eye damage	
Specific target organ toxicity	: Category 3	May cause resp	biratory irritation	
(single exposure)		May cause drow	vsiness or dizziness	
Carcinogenicity	•	,	component that is considered GIH, OSHA or NTP .	

SECTION 12: Ecological information

12.1. Ecotoxicity	: No data available
12.2. Persistence and degradability	: No data available
12.3. Bioaccumulative potential	: No data available
12.4. Mobility in soil	: No data available
12.5. Other adverse effects	: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal must be made according to official regulations. Comply with all Federal, State, and Local regulations regarding disposal. Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

14.1. UN number	DOT, TDG, IMO / IMDG, IATA / ICAO	: UN1210	
14.2. UN proper shipping name	DOT, TDG, IMO / IMDG, IATA / ICAO	: PRINTING INK,flammable	
14.3. Transport hazard class(es)	DOT, TDG, IMO / IMDG, IATA / ICAO · Class · Label	: 3 (Flammable liquids.) 3	
14.4. Packing group	DOT, TDG, IMO / IMDG, IATA / ICAO	: 1	
14.5. Environmental hazards	Marine pollutant	: No	
14.6. Special precautions for user	EMS Number	: F-E,S-D	
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		: Not applicable.	
$\diamond \diamond$			
Artline Permanent Marker (EK-250) is	not a hazardous material by the special p	provision.	

Artline Permanent Marker (EK-250	(Amount of ink : less than 10ml)
UN number	UN3175
UN proper shipping name	Solids containing Flammable Liquid. n.o.s.
IATA	Special Provision A46
IMDG Code	Special Provision 216
ADG	Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

SECTION 15: Regulatory information

< USA Information >					
	OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.				
	TSCA inventory : All components of this product are listed in the TSCA Inventory.				
	TSCA Hazard Communication Program (40 CFR Part 721) (SNUR)	:	not Listed		
	EPCRA Section 302 Extremely Hazardous Substances (EHS)	:	not Listed		
	EPCRA Section 313 Toxic Chemicals	:	not Listed		
	CERCLA Hazardous Substances	:	not Listed		
	CAA Section 112(r) List of Substances for Accidental Release Prevention	:	not Listed		
	California Proposition 65	:	not Listed		

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Canada inventory : All components of this product are listed in the DSL/NDSL Inventory.

WHMIS Ingredient Disclosure List (SOR/88-64)

: Ethanol, 1-methoxypropan-2-ol

(WHMIS : Canadian Workplace Hazardous Material Information System)

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date Preparation Date : 20.05.2015 : 09.05.2014



EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC) This product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenylethers (PBDE).

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.