

Safety Data Sheet



According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

Revision Date : 28.05.2015

1.1. Product identifier	ation	
Product Name	: Artline WHITEBOARD MARKER Color : (Brown)	ine 500A 📓
Product Name		4974052 809866 BROW
		tline 509A
	Artline REFILL INK FOR WHITEBOARD MARKER	4974052 810077 BF
	ESK-50A,ESK-50A-30,ESK-50A-60,ESK-50A-500	Artline
1.2. Recommended use	e of the chemical and restrictions on use	
Recommended use	: Whiteboard marker ink	
1.3. Details of the suppl	ier of the safety data sheet	
Company Name	: Shachihata Inc. (U.S.A.)	
Address	: 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.	
Telephone	: 1-800-541-9719	Artline
Fax Contact (e-mail)	: 1-800-541-7166 : customerservice@xstamper.com	A Decider
Contact (e-mail)	<u>customerservice@xstamper.com</u>	
1.4. Emergency telepho		
CHEMTREC 1-80		
(For Hazardous	materials or dangerous goods incident, Spill, leak, fire, exposure or accident)	
ECTION 2: Hazard(s) identification	
United States (US) :	According to OSHA 29 CFR 1910.1200 HCS 2012	
2.1.1 Classification of th		
2.1.1 Classification of th Flammable liquids. (e substance or mixture	apour
Flammable liquids, (e substance or mixture	apour
Flammable liquids, (Serious eye damage	e substance or mixture Category 2 H225 : Highly flammable liquid and va	apour
Flammable liquids, (Serious eye damage 2.1.2 Label elements	e substance or mixture Category 2 H225 : Highly flammable liquid and va	apour
Flammable liquids, (Serious eye damage	e substance or mixture Category 2 H225 : Highly flammable liquid and va	apour
Flammable liquids, (Serious eye damage 2.1.2 Label elements	e substance or mixture Category 2 H225 : Highly flammable liquid and va	apour
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms	e substance or mixture Category 2 H225 : Highly flammable liquid and va	apour
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word	e substance or mixture Category 2 H225 : Highly flammable liquid and va a /eye irritation, Category 2B H320 : Causes eye irritation : : Danger	apour
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms	 e substance or mixture Category 2 H225 : Highly flammable liquid and value /eye irritation, Category 2B H320 : Causes eye irritation 	(H225)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word	e substance or mixture Category 2 H225 : Highly flammable liquid and va a /eye irritation, Category 2B H320 : Causes eye irritation : : Danger	
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme	 e substance or mixture Category 2 e /eye irritation, Category 2B H320 H320 Causes eye irritation 	(H225)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention]	 e substance or mixture Category 2 b /eye irritation, Category 2B c auses eye irritation c auses eye irritation c Danger c Highly flammable liquid and vapour Causes eye irritation 	(H225) (H320)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea	 e substance or mixture Category 2 H225 Highly flammable liquid and vacation Causes eye irritation Danger Highly flammable liquid and vapour Causes eye irritation nt 	(H225) (H320) (P210)
Flammable liquids, 0 Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary	 e substance or mixture Category 2 H225 Highly flammable liquid and vacation Causes eye irritation Danger Highly flammable liquid and vapour Causes eye irritation Int	(H225) (H320) (P210) (P243)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow	 Highly flammable liquid and value Highly flammable liquid and value Highly flammable liquid and value Danger Highly flammable liquid and vapour Causes eye irritation Int at/sparks/open flames/hot surfaces No smoking. measures against static discharge. ves/protective clothing/eye protection/face protection.	(H225) (H320) (P210) (P243) (P280)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o	 Highly flammable liquid and vacuum and vacuum	(H225) (H320) (P210) (P243) (P280) (P271)
Flammable liquids, 0 Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug	 Highly flammable liquid and vacuum and vacuum	(H225) (H320) (P210) (P243) (P280)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary statemen [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug [Response]	 He substance or mixture Category 2 H225 : Highly flammable liquid and variable experimitation, Category 2B H320 : Causes eye irritation 	(H225) (H320) (P210) (P243) (P280) (P271) (P264)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug [Response] In case of fire :	 He substance or mixture He substance or mixture<	(H225) (H320) (P210) (P243) (P280) (P271) (P264) (P370+P378)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug [Response] In case of fire :	 He substance or mixture Category 2 H225 : Highly flammable liquid and variable experimitation, Category 2B H320 : Causes eye irritation 	(H225) (H320) (P210) (P243) (P280) (P271) (P264)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug [Response] In case of fire : IF INHALED :	 Highly flammable liquid and value Highly flammable liquid and value Highly flammable liquid and value Causes eye irritation Line Constraints Highly flammable liquid and vapour causes eye irritation Hig	(H225) (H320) (P210) (P243) (P280) (P271) (P264) (P370+P378) (P304+P340)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug [Response] In case of fire : IF INHALED :	He substance or mixture Category 2 H225 Highly flammable liquid and vare A (eye irritation, Category 2B H320 Causes eye irritation Image: Image: Causes Image: Image: Image: Image:	(H225) (H320) (P210) (P243) (P280) (P271) (P264) (P370+P378) (P304+P340)
Flammable liquids, (Serious eye damage 2.1.2 Label elements Hazard pictograms Signal word Hazard statement Precautionary stateme [Prevention] Keep away from hea Take precautionary Wear protective glow Use only outdoors o Wash hands thoroug [Response] In case of fire : IF INHALED :	 He substance or mixture Category 2 H225 Highly flammable liquid and va Causes eye irritation Causes eye irritation Danger Highly flammable liquid and vapour Causes eye irritation It Highly flammable liquid and vapour Causes eye irritation It Highly flammable liquid and vapour Causes eye irritation It Use dry chemical powder, form or carbon dioxide for extinction. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. 	(H225) (H320) (P210) (P243) (P280) (P271) (P264) (P370+P378)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-500A_brown_b] 2/5

	Rinse skin with water/shower.	
If skin irritation occurs	: Get medical advice/attention.	(P332+P313)
IF SWALLOWED	: Get medical advice/attention if you feel unwell.Rinse mouth.	(P301+P314+P330)
[Storage]		
Store in a well-ventilated	place. Keep container tightly closed.	(P403+P233)
[Disposal]		
Dispose of contents/cont	tainer to waste in accordance with	(P501)
local/regional/ nationa	al/international regulation (to be specified).	

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada : According to WHMIS

- 2.2.1 Classification of the substance or mixture
 - Class B2 : Flammable Liquids
 - Class D2B : Eye irritation
- 2.2.2 Label elements



2.2.3 Other hazards

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS)

2.3 Other information



SECTION 3: Composition/information on ingredients

Substance/Mixture	:	Mixture
Ingredients	:	

Chemical Name /	Composition	CAS	Classification (C	SHA HCS 2012)
Generic name	weight %	Registry No.	Hazard Class	Hazard statement
Ethanol	60 ~ 70	64-17-5	Flam.Liq. 2	H225
Propan-2-ol	10 ~ 20	67-63-0	Flam.Liq. 2 Eye Irrit. 2 STOT.SE. 3	H225 H319 H336
Organic pigment	1 ~ 10	Confidential	none	none
Synthetic resin	1 ~ 10	Confidential	none	none
Additive	5 ~ 15	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of fi IF INHALED	 rst aid measures Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.
IF ON SKIN	: Remove/Take off immediately all contaminated clothing.Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.
IF IN EYES	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.Continue rinsing. If eye irritation persists, get medical advice/attention.
IF SWALLOWED	: After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach,

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-500A_brown_b] 3/5

and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide Unsuitable extinguishing media : Water jet

- 5.2. Special hazards arising from the substance or mixtureFor initial stage extinction, carbon dioxide or dry chemical powder.When a fire extends, fire is extinguished by a large amount of water spray.Do not discharge extinguishing waters into the aquatic environment.
- 5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency proceduresEvacuate personnel to safe area. Shut off all sources of ignition.No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.
- 6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning upIn case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth,etc.), and then wipe off the waste well with waste cloth, and rag.In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

7.1. Precautions for safe hand	dling
Advice on safe handling :	Use with adequate ventilation.
	Avoid contact with skin, eyes and clothing.
	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage	ge, including any incompatibilities

Requirements for storage: Keep containers tightly closed and store in a cool and dry place.areas and containersKeep away from heat and flame, ignition source and sunlight.Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2013) Ethanol Propan-2-ol	STEL TWA	1000ppm 200ppm
OSHA PEL Ethanol Propan-2-ol	TWA TWA	1000ppm 400ppm
Canada Ontario Provincial Ethanol Propan-2-ol	STEL TWA	1000ppm 200ppm
Canada Quebec Provincial Ethanol Propan-2-ol	TWA TWA	1000ppm 400ppm

8.2. Exposure controls

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-500A_brown_b] 4/5

Respiratory Protection	:	Use with local exhaust ventilation, when in long use.
------------------------	---	---

- Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
- Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.
- Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.
- Skin Protection : Avoid skin contact. Wear personal protection apron,boots,if necessary.

Environmental exposure controls

General advice

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and ch	emical properties
Appearance	: brown liquid
Odor	: minor solvent odor
рН	: Not applicable
Boiling point	: No data available
Flash point	: 55.4 °F (13 °C) (closed cup)
Relative Density (at 77 $^{\circ}$ F , 25 $^{\circ}$ C)	$: 0.8 \sim 0.9$ (g/cm ³)
Solubility in Water	: Insoluble

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

- 10.3. Chemical stability
 - The product is stable.
- 10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

- 10.5. Incompatible Materials
 - No data available
- 10.6. Hazardous decomposition products
 - CO, CO_2

SECTION 11: Toxicological information

11.1. Information on toxicological e	ffects		
Acute toxicity	: LD/LC50 values that are relevant for classification [Ethanol]		
	Oral-rat	LD50	7,060mg/kg
	Inhalation-rat [Propan-2-ol]	LC50	20,000ppm/10h
	Oral-rat Dermal-rabbit	LD50 LD50	>5,000mg/kg >5,000mg/kg
Serious eye damage /eye irritation	: Category 2B	Causes eye	irritation
Carcinogenicity	•	•	/ component that is considered CGIH, OSHA or NTP .

SECTION 12: Ecological information

12.1. Ecotoxicity : No data available
12.2. Persistence and degradability : No data available
12.3. Bioaccumulative potential : No data available
12.4. Mobility in soil : No data available
12.5. Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal must be made according to official regulations.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-500A_brown_b] 5/5

Comply with all Federal, State, and Local regulations regarding disposal. Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information							
14.1. UN number	DOT, TDG, IMO / IMDG, IATA / ICAO	: UN1210					
14.2. UN proper shipping name	DOT, TDG, IMO / IMDG, IATA / ICAO	: PRINTING INK,flammable					
14.3. Transport hazard class(es)	DOT, TDG, IMO / IMDG, IATA / ICAO · Class · Label	: 3 (Flammable liquids.) 3					
14.4. Packing group	DOT, TDG, IMO / IMDG, IATA / ICAO	: 1					
14.5. Environmental hazards	Marine pollutant	: No					
14.6. Special precautions for user	EMS Number	: F-E,S-D					
14.7. Transport in bulk according to MARPOL 73/78 and the IBC	: Not applicable.						
Artime WHITEBOARD MARKER (EK-	500A ,EK-509A ,EK-550A) is not a hazar	rdous material by the special provision.					

Artline WHITEBOARD MARKER	R (El	K-500A ,EK-509A ,EK-550A)	(The amount of ink : less than 10ml)
UN number	:	UN3175	
UN proper shipping name	:	Solids containing Flammable Liquid.	n.o.s.
ΙΑΤΑ		Special Provision A46	
IMDG Code		Special Provision 216	

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

< USA Information >	
OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.	
TSCA Hazard Communication Program (40 CFR Part 721) (SNUR)	: not Listed
EPCRA Section 302 Extremely Hazardous Substances (EHS)	: not Listed
EPCRA Section 313 Toxic Chemicals	: not Listed
CERCLA Hazardous Substances	: not Listed
CAA Section 112(r) List of Substances for Accidental Release Prevention	: not Listed
California Proposition 65	: not Listed
< Canada Information >	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

WHMIS Ingredient Disclosure List (SOR/88-64)

: Ethanol, Propan-2-ol

(WHMIS : Canadian Workplace Hazardous Material Information System)

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 28.0 Preparation Date : 02.0

: 28.05.2015 : 02.05.2014



EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC) This product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenylethers (PBDE).

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.