

# Safety Data Sheet



According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

Revision Date : 18.05.2015

SECTION 1: Identification	
1.1. Product identifier	
Product Name : Artline Permanent Marker Color : (Red) EK-30, EK-50, EK-70, EK-90, EK-100, EK-110,EK-120, EK-130, EK-700 Artline marking INK ESK-20,ESK-20-30,ESK-20-60,ESK-3,ESK-20-500	
1.2. Recommended use of the chemical and restrictions on use	Artline
Recommended use : Permanent marker ink	marking INIK
1.3. Details of the supplier of the safety data sheet	
Company Name : Shachihata Inc. (U.S.A.)	Harden Manne (MAR)
Address: 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.Telephone: 1-800-541-9719Fax: 1-800-541-7166Contact (e-mail): customerservice@xstamper.com	Artilize ;
1.4. Emergency telephone number CHEMTREC 1-800-424-9300 (For Hazardous materials or dangerous goods incident,Spill, leak, fire, exposure or accident)	
SECTION 2: Hazard(s) identification	
United States (US) : According to OSHA 29 CFR 1910.1200 HCS 2012	
Flammable liquids, Category 2 Serious eye damage /eye irritation, Category 1 2.1.2 Label elements Hazard pictograms :	
Signal word : Danger	
Hazard statement : Highly flammable liquid and vapour Causes serious eye damage	(H225) (H318)
Precautionary statement [Prevention]	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	(P210)
Take precautionary measures against static discharge.	(P243)
Wear protective gloves/protective clothing/eye protection/face protection.	(P280)
Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. 【Response】	(P271) (P264)
In case of fire : Use dry chemical powder, form or carbon dioxide for extinction.	(P370+P378)
<ul> <li>IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.</li> <li>IF IN EYES : Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses if present and easy to do. Continue rinsing.</li> </ul>	(P304+P340) (P305+P351+P338)
Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists : Get medical advice/attention.	(P337+P313)
IF ON SKIN (or hair) : Remove/Take off immediately all contaminated clothing.	(P303+P361+P353)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [ESK-20\_red\_d] 2/6

	Rinse skin with water/shower.	
If skin irritation occurs	: Get medical advice/attention.	(P332+P313)
IF SWALLOWED	: Get medical advice/attention if you feel unwell.Rinse mouth.	(P301+P314+P330)
[Storage]		
Store in a well-ventilated	place. Keep container tightly closed.	(P403+P233)
[Disposal]		
Dispose of contents/cont	tainer to waste in accordance with	(P501)
local/regional/ nationa	al/international regulation (to be specified).	

#### 2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

#### Canada : According to WHMIS


- 2.2.1 Classification of the substance or mixture
  - Class B2 : Flammable Liquids
  - Class D2B : Eye irritation
- 2.2.2 Label elements



#### 2.2.3 Other hazards

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS)

#### 2.3 Other information



## SECTION 3: Composition/information on ingredients

Substance/Mixture	:	Mixture
Ingredients	:	

Chemical Name /	Chemical Name / Composition CAS	Classification (OSHA HCS 2012)		
Generic name	weight %	Registry No.	Hazard Class	Hazard statement
Ethanol	50 ~ 60	64-17-5	Flam.Liq. 2	H225
Propan-1-ol	5 ~ 15	71-23-8	Flam.Liq. 2 Eye Dam. 1 STOT.SE. 3	H225 H318 H336
Ethyl lactate	10 ~ 20	97-64-3	Flam.Liq. 3 Eye Dam. 1 STOT.SE. 3	H226 H318 H335
Benzyl alcohol	1 ~ 5	100-51-6	Acute Tox.(oral) 4 Acute Tox.( inhal.) 4	H302 H332
Synthetic resin	5 ~ 15	Confidential	none	none
Dyestuff	5 ~ 10	Confidential	none	none
total	100			

# **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.

- IF ON SKIN
- : Remove/Take off immediately all contaminated clothing. Wash with soap and water.

#### [ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [ESK-20\_red\_d] 3/6

If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

- IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.Continue rinsing.If eye irritation persists, get medical advice/attention.
- IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly.Moreover, do not give anything from the mouth to the patient when not conscious.Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

#### SECTION 5: Fire-fighting measures

- 5.1. Extinguishing media
   Suitable extinguishing media
   Dry chemical powder, foam or carbon dioxide
   Unsuitable extinguishing media
   Water jet
- 5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder. When a fire extends, fire is extinguished by a large amount of water spray. Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

## SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
 Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth,etc.), and then wipe off the waste well with waste cloth, and rag. In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

## SECTION 7: Handling and storage

8.

7.1. Precautions for safe handling

Advice on safe handling
Use with adequate ventilation.
Avoid contact with skin, eyes and clothing.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage: Keep containers tightly closed and store in a cool and dry place.areas and containersKeep away from heat and flame,ignition source and sunlight.Keep out of the reach of children.

## SECTION 8: Exposure controls/personal protection

.1. Control parameters		
ACGIH (2013)		
Ethanol	STEL	1000ppm
Propan-1-ol	TWA	100ppm
OSHA PEL		
Ethanol	TWA	1000ppm
Propan-1-ol	TWA	200ppm
Canada Ontario Provincial		
Ethanol	STEL	1000ppm
Propan-1-ol	TWA	100ppm

Canada Quebec Provincial		
Ethanol	TWA	1000ppm
Propan-1-ol	TWA	200ppm

8.2. Exposure controls	
Personal protective equipm	ent
Respiratory Protection	: Use with local exhaust ventilation, when in long use.
	Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
Hand Protection	: Avoid contact with hands. Wear safety gloves, if necessary.
Eye Protection	: Avoid contact with eyes. Wear safety glasses, if necessary.
Skin Protection	: Avoid skin contact. Wear personal protection apron, boots, if necessary.
Environmental exposure co	ontrols
General advice	: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and ch Appearance	emical properties : red liquid
Odor	: minor solvent odor
рН	: Not applicable
Boiling point	: No data available
Flash point	: 61.7 °F (16.5 °C) (closed cup)
Relative Density (at 77 °F , 25 °C)	$: 0.85 \sim 0.95$ (g/cm <sup>3</sup> )
Solubility in Water	: Insoluble

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

- 10.3. Chemical stability
- The product is stable.
- 10.4. Conditions to Avoid
- High temperature, Direct sunlight, Fire
- 10.5. Incompatible Materials
  - No data available
- 10.6. Hazardous decomposition products
  - $CO, CO_2$

## SECTION 11: Toxicological information

11.1. Information on toxicological effects Acute toxicity : LD/LC50 values that are relevant for classification [Ethanol] Oral-rat LD50 7,060mg/kg 20,000ppm/10h Inhalation-rat LC50 [Propan-1-ol] Oral-rat LD50 1,870mg/kg Dermal-rabbit LD50 4,060mg/kg 4,000mg/l/4H Inhalation-rat LC50 [Ethyl lactate] Oral-rat LD50 2,500mg/kg Inhalation-rat LC50 >5,400mg/m<sup>3</sup>/8H [Benzyl alcohol] Oral-rat LD50 1,610mg/kg Dermal-rabbit LD50 2,000mg/kg Inhalation-rat LC50 >4,178mg/l/4H Serious eye damage /eye irritation : Category 1 Causes serious eye damage Carcinogenicity : This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, OSHA or NTP.

## SECTION 12: Ecological information

12.1. Ecotoxicity	: No data available
12.2. Persistence and degradability	: No data available
12.3. Bioaccumulative potential	: No data available
12.4. Mobility in soil	: No data available
12.5. Other adverse effects	: No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal must be made according to official regulations. Comply with all Federal, State, and Local regulations regarding disposal. Do not allow product to reach ground, any water course or sewage system.

#### **SECTION 14: Transport information**

14.1. UN number	DOT, TDG, IMO / IMDG, IATA / ICAO	:	UN1210	
14.2. UN proper shipping name	DOT, TDG, IMO / IMDG, IATA / ICAO	:	PRINTING INK,flammable	
14.3. Transport hazard class(es)	DOT, TDG, IMO / IMDG, IATA / ICAO · Class · Label	:	3 (Flammable liquids.) 3	
14.4. Packing group	DOT, TDG, IMO / IMDG, IATA / ICAO	:	Π	•
14.5. Environmental hazards	Marine pollutant	:	No	
14.6. Special precautions for user	EMS Number	:	F-E,S-D	
14.7. Transport in bulk according to MARPOL 73/78 and the IBC		:	Not applicable.	

#### ☆☆

Artline Permanent Marker (EK-30,EK-70,EK-90,EK-700) is not a hazardous material by the special provision. However, Artline Permanent Marker (EK-50,EK-100,EK-110,EK-120,EK-130) is a hazardous material (UN3175) for more than 10ml.

Artline Permanent Marker(EK-30	),EK-70,EK-90,EK-700)	(Amount of ink : less than 10ml )
UN number	: UN3175	
UN proper shipping name	: Solids containing Flammat	ble Liquid. n.o.s.
ΙΑΤΑ	Special Provision A46	
IMDG Code	Special Provision 216	
sealed packets and articles c	ontaining less than 10 mL of a	Special Provision 216, small inner packagings consisting of Class 3 liquid in Packing Group II or III absorbed onto a Igerous goods provided there is no free liquid in the
Artline Permanent Marker (EK-	50,EK-100,EK-110,EK-120,EK-	130) (Amount of ink : over 10ml)
UN number	: UN3175	
UN proper shipping name	: Solids containing Flammat	ble Liquid. n.o.s.
UN Classification	: 4.1	
Packing group	: I	

## SECTION 15: Regulatory information

<	USA Information >			
	OSHA STATUS :	This product is hazardous under 29 CFR 1910.1200	).	
	TSCA inventory :	All components of this product are listed in the TSC.	ΑI	nventory.
	TSCA Hazard Commu	nication Program (40 CFR Part 721) (SNUR)	:	not Listed
	EPCRA Section 302 E	xtremely Hazardous Substances (EHS)	:	not Listed
	EPCRA Section 313 T	oxic Chemicals	:	not Listed
	CERCLA Hazardous S	Substances	:	not Listed
	CAA Section 112(r) Lis	st of Substances for Accidental Release Prevention	:	not Listed
	California Proposition	65	:	not Listed

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [ESK-20\_red\_d] 6/6

(WHMIS : Canadian Workplace Hazardous Material Information System)

Canada inventory : All components of this product are listed in the DSL/NDSL Inventory.

WHMIS Ingredient Disclosure List (SOR/88-64)

: Ethanol, Propan-1-ol, Benzyl alcohol

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 18.05.2015

Preparation Date : 26.09.2013



EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC) This product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenylethers (PBDE).

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.