

Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

SECTION 1: Identification

1.1. Product identifier

1.2.

| Product Name | : TAT INDELIBLE INK (Quick Dry) Multipurpose | |
|---|--|--|
| | $STSG,\ STSG-1 (\text{Small bottle}),\ STSG-3 (\text{Large bottle})$ | |
| Recommended use of the chemical and restrictions on use | | |

Recommended use : Stamp ink

1.3. Details of the supplier of the safety data sheet

| Company Name | : Shachihata Inc. (U.S.A.) |
|------------------|--|
| Address | : 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A. |
| Telephone | : 1-800-541-9719 |
| Fax | : 1-800-541-7166 |
| Contact (e-mail) | : <u>customerservice@xstamper.com</u> |

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300

(For Hazardous materials or dangerous goods incident, Spill, leak, fire, exposure or accident)

SECTION 2: Hazard(s) identification

United States (US) : According to OSHA 29 CFR 1910.1200 HCS 2012

| 2.1.1 | Classification of the substance or mixture |
|-------|--|
| | Flammable liquids, Category 3 |
| | Serious eye damage /eye irritation, Category 2B |
| | Specific target organ toxicity ; single exposure, Category 3 |
| | (respiratory tract irritation, narcotic effects) |
| | |

:

H226 : Flammable liquid and vapour

Color : (Black)

- H320 : Causes eye irritation
- H335 : May cause respiratory irritation
- H336 : May cause drowsiness or dizziness

2.1.2 Label elements

Hazard pictograms



| Signal word | : | Warning | |
|------------------|---|-----------------------------------|--------|
| Hazard statement | : | Flammable liquid and vapour | (H226) |
| | | Causes eye irritation | (H320) |
| | | May cause respiratory irritation | (H335) |
| | | May cause drowsiness or dizziness | (H336) |

Precautionary statement

| [Prevention] | | |
|--|--|------------------|
| Keep away from | (P210) | |
| Take precaution | (P243) | |
| Wear protective | (P280) | |
| Avoid breathing | dust/fume/gas/mist/vapours/spray. | (P261) |
| Use only outdoo | rs or in a well-ventilated area. | (P271) |
| Wash hands thoroughly after handling. | | (P264) |
| [Response] | | |
| In case of fire | : Use dry chemical powder, form or carbon dioxide for extinction. | (P370+P378) |
| IF INHALED | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. | (P304+P340) |
| IF IN EYES | : Rinse cautiously with water for several minutes. | (P305+P351+P338) |
| | Remove contact lenses, if present and easy to do. Continue rinsing. | |
| If eye irritation persists : Get medical advice/attention. | | (P337+P313) |
| IF ON SKIN (or | (P303+P361+P353) | |







Revision Date : 18.05.2015

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [STSG_black_c] 2/5

| | Rinse skin with water/shower. | |
|----------------------------|--|------------------|
| If skin irritation occurs | : Get medical advice/attention. | (P332+P313) |
| IF SWALLOWED | : Get medical advice/attention if you feel unwell.Rinse mouth. | (P301+P314+P330) |
| [Storage] | | |
| Store in a well-ventilated | l place. Keep container tightly closed. | (P403+P233) |
| [Disposal] | | |
| Dispose of contents/cont | tainer to waste in accordance with | (P501) |
| local/regional/ nationa | al/international regulation (to be specified). | |
| | | |

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada : According to WHMIS

- 2.2.1 Classification of the substance or mixture
 - Class B2 : Flammable Liquids
 - Class D2B : Eye irritation
- 2.2.2 Label elements



2.2.3 Other hazards

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS)

2.3 Other information



SECTION 3: Composition/information on ingredients

Substance/Mixture : Mixture Ingredients :

| Chemical Name / | Composition | CAS | Classification (C | SHA HCS 2012) |
|---------------------------------|-------------|--------------|---|----------------------|
| Generic name | weight % | Registry No. | Hazard Class | Hazard statement |
| 1-ethoxypropan-2-ol | 50 ~ 60 | 1569-02-4 | Flam.Liq.3 Eye Irrit.2B STOT.SE.3 | H226 H320 H336 |
| (2-methoxymethylethoxy)propanol | 20 ~ 30 | 34590-94-8 | Flam.Liq.4 STOT.SE.3 | H227 H335 |
| Synthetic resin | 10 ~ 20 | Confidential | none | none |
| Carbon black | 1 ~ 10 | 1333-86-4 | none | none |
| total | 100 | | | |

SECTION 4: First-aid measures

4.1. Description of first aid measures

| IF INHALED | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist. |
|--------------|---|
| IF ON SKIN | : Remove/Take off immediately all contaminated clothing.Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice. |
| IF IN EYES | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.Continue rinsing. If eye irritation persists, get medical advice/attention. |
| IF SWALLOWED | : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, |

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [STSG_black_c] 3/5

and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide Unsuitable extinguishing media : Water jet

- 5.2. Special hazards arising from the substance or mixtureFor initial stage extinction, carbon dioxide or dry chemical powder.When a fire extends, fire is extinguished by a large amount of water spray.Do not discharge extinguishing waters into the aquatic environment.
- 5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency proceduresEvacuate personnel to safe area. Shut off all sources of ignition.No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.
- 6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up
In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth,etc.), and then wipe off the waste well with waste cloth, and rag.
In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

8.1

Requirements for storage
areas and containers: Keep containers tightly closed and store in a cool and dry place.Keep away from heat and flame,ignition source and sunlight.
Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

| 1. Control parameters ACGIH (2013) | |
|---------------------------------------|-----------------------|
| (2-methoxymethylethoxy)propanol TWA | 100ppm |
| Carbon black TWA | 3 mg/m ³ |
| OSHA PEL | |
| (2-methoxymethylethoxy)propanol TWA | 100ppm |
| Carbon black TWA | 3.5 mg/m ³ |
| Canada Ontario Provincial | |
| (2-methoxymethylethoxy)propanol TWA | 100ppm |
| Carbon black TWA | 3.5 mg/m ³ |
| Canada Quebec Provincial | |
| (2-methoxymethylethoxy)propanol TWA | 100ppm |
| Carbon black TWA | 3.5 mg/m ³ |

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [STSG_black_c] 4/5

8.2. Exposure controls

| Personal protective equipm | | |
|--|--|--|
| Respiratory Protection : Use with local exhaust ventilation, when in long use. | | |
| | d breathing vapours. Wear mask to prevent organic gas, if necessary. | |
| Hand Protection | d contact with hands. Wear safety gloves, if necessary. | |
| Eye Protection | d contact with eyes. Wear safety glasses, if necessary. | |
| Skin Protection | d skin contact. Wear personal protection apron,boots,if necessary. | |
| Environmental exposure co | | |
| 0 1 1 1 | | |

 General advice
 : Prevent product from entering drains.

 Prevent further leakage or spillage if safe to do so.

 If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical and chemical properties | | | |
|---|----------------------------------|--|--|
| Appearance | : black liquid | | |
| Odor | : minor solvent odor | | |
| рН | : Not applicable | | |
| Boiling point | : No data available | | |
| Flash point | : 105.8 °F (41 °C) (closed cup) | | |
| Relative Density (at 77 °F , 25 °C) | : 1.0 ~ 1.1 (g/cm ³) | | |
| Solubility in Water | : Insoluble | | |
| | | | |

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

- 10.3. Chemical stability
- The product is stable.
- 10.4. Conditions to Avoid High temperature, Direct sunlight, Fire
- 10.5. Incompatible Materials
- No data available
- 10.6. Hazardous decomposition products
 - CO, CO₂


SECTION 11: Toxicological information

| 11.1. Information on toxicological e | ffects | | |
|--------------------------------------|--|-----------------------------------|---------------|
| Acute toxicity | : LD/LC50 values that are relevant for classification [1-ethoxypropan-2-ol] | | |
| | | | |
| | Oral-rat | LD50 | >5,000mg/kg |
| | Inhalation-rat | LC50 | >10,000ppm/4H |
| | Dermal-rabbit | LD50 | 9ml/kg |
| | [(2-methoxymethylethoxy)propanol] | | |
| | Oral-rat | LD50 | 5,180mg/kg |
| | Dermal-rabbit | LD50 | 9,500mg/kg |
| Serious eye damage /eye irritation | : Category 2B | Causes eye irritation | |
| Specific target organ toxicity | : Category 3 | May cause respiratory irritation | |
| | | May cause drowsiness or dizziness | |
| 8 3 | ck has been classified | 5 | 1 |

Other materials ; Not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP .

Regarding the carcinogenicity of carbon black, International Agency for Research on Cancer (IARC) has classified as a group 2B. However, ACGIH(American Conference of Governmental Industrial Hygienists) ,EPA(Environmental Protection Agency),EU (European Chemicals Agency), NTP (National Toxicology Program, USA) in the classification of suspected carcinogenic to humans has not been done. Therefore, as the ink product we could not classify the carcinogenicity of GHS from that there is no sufficient data.

SECTION 12: Ecological information 12.1. Ecotoxicity : No data available : No data available 12.2. Persistence and degradability : No data available 12.3. Bioaccumulative potential 12.4. Mobility in soil : No data available 12.5. Other adverse effects : No known significant effects or critical hazards. SECTION 13: Disposal considerations 13.1. Waste treatment methods Disposal must be made according to official regulations. Comply with all Federal, State, and Local regulations regarding disposal. Do not allow product to reach ground, any water course or sewage system. SECTION 14: Transport information 14.1. UN number DOT, TDG, IMO / IMDG, IATA / ICAO : UN1210 14.2. UN proper shipping name DOT, TDG, IMO / IMDG, IATA / ICAO : PRINTING INK, flammable 14.3. Transport hazard class(es) DOT, TDG, IMO / IMDG, IATA / ICAO · Class 3 (Flammable liquids.) Label 3 DOT, TDG, IMO / IMDG, IATA / ICAO : 1 14.4. Packing group Marine pollutant 14.5. Environmental hazards : No 14.6. Special precautions for user **EMS Number** : F-E,S-D 14.7. Transport in bulk according to Annex II of : Not applicable. MARPOL 73/78 and the IBC Code SECTION 15: Regulatory information < USA Information > **OSHA STATUS** : This product is hazardous under 29 CFR 1910.1200. : All components of this product are listed in the TSCA Inventory. **TSCA** inventory TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : not Listed EPCRA Section 302 Extremely Hazardous Substances (EHS) : not Listed **EPCRA Section 313 Toxic Chemicals** : not Listed **CERCLA Hazardous Substances** : not Listed CAA Section 112(r) List of Substances for Accidental Release Prevention : not Listed California Proposition 65 listed [carbon black] < Canada Information > This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. Canada inventory : All components of this product are listed in the DSL/NDSL Inventory. WHMIS Ingredient Disclosure List (SOR/88-64) : 1-ethoxypropan-2-ol (WHMIS : Canadian Workplace Hazardous Material Information System) (2-methoxymethylethoxy)propanol SECTION 16: Other information, including date of preparation or last revision Last Revision Date 18.05.2015 Preparation Date : 02.10.2013 RoHS EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC) ELV



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

compliant